



M4FOUR | International BV  
 A. Plesmanlaan 13  
 9615 TJ Kolham  
 The Netherlands


T +31(0)85 273 01 85  
 Info@M4FOUR.com

# Prem-D



## PREM-D PRODUCT INFORMATION

Usage classification	EN ISO 10874 / EN 685		22+ Domestic General
Wear layer	EN ISO 24340 / EN 4291		0.225 mm
Total thickness	EN ISO 24346 / EN 428		2.00 mm
Total weight	EN ISO 23997 / EN 430		1280 g/m <sup>2</sup>
Standard widths	EN ISO 24341 / EN 426		4 m
Standard length	EN ISO 24341 / EN 426		30 m



## Technical Information

Light stability	EN ISO 105 B02		≥ 7
Dimensional Stability	EN ISO 23999 / EN 434		≤ 0.40 %
Thermal resistance	ISO 8302		R=0.018m <sup>2</sup> .k/W
Residual Indentation	EN ISO 24343-2 / EN 433		≤ 0.35 mm
Reaction to fire	EN 13501-1		Bfl/S1
Slip resistance	DIN 51130		R10
Dynamic coefficient of friction	EN 13893		>0.3
Impact sound	EN ISO 717/2		Δ Lw 10 dB
Simulated movement of leg furniture	EN 424		no damage with foot 3