



M4FOUR | International BV  
 A. Plesmanlaan 13  
 9615 TJ Kolham  
 The Netherlands


T +31(0)85 273 01 85  
 Info@M4FOUR.com

PRO



Technical specifications (PRO meets the requirements of ISO 10582 and EN 649)

Total thickness	ISO 24346 / EN 428		2.0 mm
Wear layer thickness	ISO 24340 / EN 429		0.7 mm
Collection size			113
Commercial use	ISO 10874 / EN 685		34 very heavy
Industrial use	ISO 10874 / EN 685		43 heavy
Roll width	ISO 24341 / EN 426		3,95 m
Roll length	ISO 24341 / EN 426		± 25 m
Total weight	ISO 23997 / EN 430		2.8 kg/m <sup>2</sup>
Dimensional stability	ISO 23999 / EN 434		< 0.1%
Residual indentation	ISO 24343-1 / EN 433		≤ 0.05 mm
Abrasion resistance	EN 660-2		group T
Castor chair continuous use	ISO 4918 / EN 425		no effect
Light fastness	ISO 105-B02		≥ 6
Flexibility	ISO 24344 / EN 435		ø 10 mm
Resistance to chemicals	ISO 26787 / EN 423		very good
Slip resistance	DIN 51130		R10
Electrical resistance	EN 1081		R1 > 1.10 <sup>9</sup> Ω
Suitable for floor heating			Yes*
Wetroom certification	EN 13553		Yes



All PRO products meet the requirements of EN 14041



Reaction to fire	EN 13501-1		B <sub>fl</sub> -s1
Slip resistance	EN 13893		DS - μ ≥ 0.30
Body voltage	EN 1815		≤ 2 kV
Thermal conductivity	EN 12524		0.25 W/m-K

\* Temperature < 30°C